



特点：

- YUJ系列为单相电阻起动电动机
- 仅适用于对起动转矩要求不大的机械
- 如小型机床、鼓风机、医疗器械等



Features :

- IEC standard design
- Apply to fans/blowers, pump ,compressor and etc
- Mounting: B3, B14, B34, B5, B35




型号	功率	转速	机座	电压	满负荷电流	频率	绝缘等级	过载系数	防护等级	工作制	重量
GW REF. NO.	HP/KW	RPM	FRAME	VOLTAGE	FLA	FREQ	INS.	S.F.	IP CODE	DUTY	WGT LB/KG
YUJ7114	0.16/0.12	1400	71	220	1.81	50	B	1.0	55	CONT	12.3/5.6
YUJ7112	0.24/0.18	2800	71	220	1.96	50	B	1.0	55	CONT	12.8/5.8
YUJ7124	0.24/0.18	1400	71	220	2.49	50	B	1.0	55	CONT	13.9/6.3
YUJ7122	0.34/0.25	2800	71	220	2.54	50	B	1.0	55	CONT	14.3/6.5
YUJ8014	0.34/0.25	1400	80	220	3.38	50	B	1.0	55	CONT	18.5/8.4
YUJ8012	0.50/0.37	2800	80	220	3.63	50	B	1.0	55	CONT	18.7/8.5
							B	1.0	55		
YUJ8022	0.75/0.55	2800	80	220	5.47	50	B	1.0	55	CONT	22.0/10.0



外形和尺寸 LAYOUT & DIMENSIONS




YUJ-B3





机座 Frame	安装尺寸 Mounting Dimensions (mm)										外形尺寸 Overall Installation Dimension			
	A	B	C	D	DH	E	F	G	H	K	AB	AC	AD	L
71	112	90	45±1.5	14 ^{+0.008} _{-0.003}	M5*12.5	30±0.260	5 ⁰ _{-0.030}	11 ⁰ _{-0.10}	71 ⁰ _{-0.5}	7 ^{+0.360} ₀	136	141	116	240
80	125	100	50±1.5	19 ^{+0.009} _{-0.004}	M6*16	40±0.310	6 ⁰ _{-0.030}	15.5 ⁰ _{-0.10}	80 ⁰ _{-0.5}	10 ^{+0.360} ₀	154	159	126.5	282




YUJ-B5



机座 Frame	法兰 Flange	安装尺寸 Mounting Dimensions (mm)										外形尺寸 Overall Installation Dimension		
		D	DH	E	F	G	M	N	P	S	T	AC	AD	L
71	FF130	14 ^{+0.008 -0.003}	M5*12.5	30±0.260	5 ^{0 -0.030}	11 ^{0 -0.10}	130	110 ^{+0.013 -0.009}	160	10 ^{+0.360 0}	3.5 ^{0 -0.120}	141	116	240
80	FF165	19 ^{+0.009 -0.004}	M6*16	40±0.310	6 ^{0 -0.030}	15.5 ^{0 -0.10}	165	130 ^{+0.013 -0.009}	200	12 ^{+0.430 0}	3.5 ^{0 -0.120}	159	126.5	282



YUJ-B14



机座 Frame	法兰 Flange	安装尺寸 Mounting Dimensions (mm)										外形尺寸 Overall Installation Dimension		
		D	DH	E	F	G	M	N	P	S	T	AC	AD	L
71	FT85	14 ^{+0.008} _{-0.003}	M5*12.5	30±0.260	5 ⁰ _{-0.030}	11 ⁰ _{-0.10}	85	70 ^{+0.012} _{-0.007}	105	M6	2.5 ⁰ _{-0.120}	141	116	240
80	FT100	19 ^{+0.009} _{-0.004}	M6*16	40±0.310	6 ⁰ _{-0.030}	15.5 ⁰ _{-0.10}	100	80 ^{+0.012} _{-0.007}	120	M6	3.0 ⁰ _{-0.120}	159	126.5	282

*以上数据仅供参考，可根据要求定制。